



DOWEX MAC-3

A Macroporous Weak Acid Cation Exchange Resin used for Water Softening, Dealkalization and Demineralization Applications

Product	Type	Matrix	Functional group
DOWEX [®] MAC-3	Weak acid cation	Polyacrylic, macroporous	Carboxylic acid

Guaranteed Sales Specifications		H ⁺ form
Total exchange capacity, min.	eq/l	3.8
	kg/ft ³ as CaCO ₃	83.0
Bead size distribution range [†] 0.3 mm - 1.2 mm, min. (50 mesh - 16 mesh)	%	90

Typical Physical and Chemical Properties		H ⁺ form
Water content	%	44 - 50
Whole beads	%	95 - 100
Total swelling (H ⁺ → Ca ⁺⁺)	%	15
Particle density	g/ml	1.18
Shipping weight	g/l	750
	lbs/ft ³	47

Recommended Operating Conditions	• Maximum operating temperature	120°C (250°F)
	• pH range	5 - 14
	• Bed depth, min.	800 mm (2.6 ft)
	• Flow rates:	
	Service/fast rinse	5-50 m/h (2-20 gpm/ft ²)
	Backwash	See figure 1
	Regeneration/displacement rinse	1-10 m/h HCl (0.4-4 gpm /ft ²), 5-20 m/h H ₂ SO ₄ (2-8 gpm /ft ²)
	Rinse	5-20 m/h (2-8 gpm /ft ²)
• Total rinse requirement	3 - 6 Bed volumes	
• Regenerant	1 - 5% HCl or 0.5 - 0.8% H ₂ SO ₄	

[†] For additional particle size information, please refer to Particle Size Distribution Cross Reference Chart (Form No. 177-01775).

Typical properties and applications

DOWEX MAC-3 weak acid cation resin has high exchange capacity, excellent regeneration efficiency, very good resistance to osmotic shock, plus good chemical and physical stability.

DOWEX MAC-3 resin is effective in removal of temporary hardness (hardness associated with alkalinity) and dealkalization. It is also used for recovery of metals. DOWEX MAC-3 resin can be supplied on request for use in food and potable water applications in accordance to the TOC (Total Organic Carbon) requirements of the major European legislations. In such cases, a recommendation is given for resin conditioning before use.

Packaging

25 liter bags or 5 cubic feet fiber drums

Figure 1. Backwash Expansion Data





Figure 2. Pressure Drop Data



DOWEX Ion Exchange Resins

For more information about DOWEX resins, call the Dow Liquid Separations business:

North America: 1-800-447-4369
 Latin America: (+55) 11-5188-9277
 Europe: (+32) 3-450-2240
 Japan: (+81) 3-5460-2100
 Australia: (+61) 3-9226-3545
<http://www.dowex.com>

Warning: Oxidizing agents such as nitric acid attack organic ion exchange resins under certain conditions. This could lead to anything from slight resin degradation to a violent exothermic reaction (explosion). Before using strong oxidizing agents, consult sources knowledgeable in handling such materials.

Notice: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

