

PARK elosztó rendszerek

1/2005

Oldal: - 1 of 2 -

Cikkszám	Type	Pieces	for Tanktype -
----------	------	--------	----------------

Distribution System VS 2,5"

Distributionsystem for tanks with 2 1/2" opening, consists top + bottom nozzle, adapter and riser pipe, not assemb.

420 310	VS 2,5" -xx22	compl.	for RT xx22, adapter w. fill cap
420 320	VS 2,5" -xx36	compl.	for RT xx30, adapter w. fill cap
420 330	VS 2,5" -xx48	compl.	for RT xx36, adapter w. fill cap
420 340	VS 2,5" -xx65	compl.	for RT xx42, adapter w. fill cap

Distribution System AKD 2,5"

Distributionsys. for tanks w.2 1/2" opening, consists top + bottom nozzle, adapter and riser pipe, not assemb.

420 350	AKD 2 1/2" -xx22	compl.	for RT xx22
420 355	AKD 2 1/2" -xx36	compl.	for RT xx36
420 360	AKD 2 1/2" -xx48	compl.	for RT xx48
420 365	AKD 2 1/2" -xx65	compl.	for RT xx65

Distribution System VS 4,5"

Distributionsys. for tanks w.4 1/2" opening, consists top + bottom nozzle, adapter and riser pipe, not assemb.

420 383	VS 4,5" -xx36	kompl.	RT xx36
420 388	VS 4,5" -xx52	kompl.	RT xx52
420 391	VS 4,5" -xx65	kompl.	RT xx53

Distribution System DSAO

Distribution System for tanks with 4 1/2" or 6" thread / flange opening, consists one Adapter toP nozzle siltwidth 0,2 or 0,5 mm; Connections to piping as described, material PVC

420 392	DSAO 16 / 4520 - 2" - 0.2 A	compl.	for RT 16
420 393	DSAO 24 / 4520 - 2" - 0.2 A	compl.	for RT 20, RT 22 and RT24
420 395	DSAO 36 / 6020 - 2" - 0.2 A	compl.	for RT 24, RT 30 and RT 36
420 396	DSAO 36 / 6030 - 3" - 0.2 A	compl.	for RT 30 and RT 36
420 397	DSAO 36 / 6020 - F 2" - 0.2 A	compl.	for RT 30 and RT 36
420 399	DSAO 48 / 6030 - F 3" - 0.2 A	compl.	for RT 42 and RT 48
420 471	DSAOB 30 / 6020 - F 2" -0.2 A	compl.	for RT 24xx, RT 30xx and RT 36xx
420 472	DSAOB 48 / 6030 - F 3" -0.2 A	compl.	for RT 42xx and RT 48xx

Distribution System DSAU

Distribution System for tanks w. 4 1/2" or 6" thread/flange opening, consists one Adapter bottUm nozzles and lateral siltwidth 0,2 or 0,5 mm; Connections to piping as described, material PVC

for 4 1/2" thread opening

420 400	DSAU 16 / 4520 - 2" - 0.2 A	compl.	for RT 16
420 410	DSAU 20 / 4520 - 2" - 0.2 A	compl.	for RT 20
420 420	DSAU 22 / 4520 - 2" - 0.2 A	compl.	for RT 22
420 430	DSAU 24 / 4520 - 2" - 0.2 A	compl.	for RT 24

for 6" thread opening

420 435	DSAU 24 / 6020 - 2" - 0.2 A	compl.	for RT 24
420 440	DSAU 30 / 6020 - 2" - 0.2 A	compl.	for RT 30
420 450	DSAU 36 / 6020 - 2" - 0.2 A	compl.	for RT 36
420 445	DSAU 30 / 6030 - 3" - 0.2 A	compl.	for RT 30
420 455	DSAU 36 / 6030 - 3" - 0.2 A	compl.	for RT 36

PARK elosztó rendszerek

1/2005

oldal: - 2 of 2 -

Art.No	Type	Pieces	for Tanktype -
--------	------	--------	----------------

Distribution System DSAU **Installationtype A**
Distribution System for tanks w. 4 1/2" or 6" thread/flange opening, consists one Aadapter bottUm nozzles and lateral siltwidth **0,2** or 0,5 mm; Connections to piping as described, material PVC

for 6" - flange opening

420 456	DSAU 30 / 6020 - F 2" - 0.2 A	compl.	for RT 30
420 457	DSAU 36 / 6020 - F 2" - 0.2 A	compl.	for RT 36
420 460	DSAU 42 / 6030 - F 3" - 0.2 A	compl.	for RT 42
420 465	DSAU 48 / 6030 - F 3" - 0.2 A	compl.	for RT 48
420 475	DSAUB 24 / 6020-F2" - 0.2 A	compl.	for RT 24
420 476	DSAUB 30 / 6020-F2" - 0.2 A	compl.	for RT 30
420 477	DSAUB 36 / 6020 - F2" - 0.2 A	compl.	for RT 36
420 478	DSAUB 42 / 6030 - F 3" - 0.2 A	compl.	for RT 42
420 479	DSAUB 48 / 6030 - F 3" - 0.2 A	compl.	for RT 48

DSAOS Distributionsystem for sideconnection , top, complete for tanksize **XX**, **Installationtype A**
siltwidth **0,2** or 0,5 mm; Connections to piping as described, not assembled

420 490	DASOS 24 / 2S - 0.2 A	compl.	für seitliche Öffnung 2"	für RT 24
420 491	DASOS 30 / 2S - 0.2 A	compl.	für seitliche Öffnung 2"	für RT 30
420 492	DSAOS 36 / 2S - 0.2 A	compl.	für seitliche Öffnung 2"	für RT 36
420 493	DSAOS 42 / 3S - 0.2 A	compl.	für seitliche Öffnung 3"	für RT 42
420 494	DSAOS 48 / 3S - 0.2 A	compl.	für seitliche Öffnung 3"	für RT 48

DS AUS Distributionsystem for sideconnection , bottom, complete for tanksize **XX**, **Installationtype A**
siltwidth **0,2** or 0,5 mm; Connections to piping as described, not assembled

420 495	DASUS 24 / 2S - 0.2 A	compl.	für seitliche Öffnung 2"	für RT 24
420 496	DASUS 30 / 2S - 0.2 A	compl.	für seitliche Öffnung 2"	für RT 30
420 497	DS AUS 36 / 2S - 0.2 A	compl.	für seitliche Öffnung 2"	für RT 36
420 498	DS AUS 42 / 3S - 0.2 A	compl.	für seitliche Öffnung 3"	für RT 42
420 499	DS AUS 48 / 3S - 0.2 A	compl.	für seitliche Öffnung 3"	für RT 48

Distribution System DSB **Installationtype B**
Distribution System for tanks with 4 1/2" or 6" opening, consists one Bottom nozzles and lateral system siltwidth **0,2** or 0,5 mm; Connections to piping as described, not assembled

420 480	DSB 16 / 2" - 0.2	compl.	for opening 4,5"
420 481	DSB 20 / 2" - 0.2	compl.	for opening 4,5"
420 482	DSB 22 / 2" - 0.2	compl.	for opening 4,5"
420 483	DSB 24 / 2" - 0.2	compl.	for opening 4,5"
420 484	DSB 30 / 2" - 0.2	compl.	for opening 6"
420 485	DSB 36 / 2" - 0.2	compl.	for opening 6"
420 486	DSB 42 / 3" - 0.2	compl.	for opening 6" - flange
420 487	DSB 48 / 2" - 0.2	compl.	for opening 6" - flange

- all filternozzles Systems can be on request also be supplied with nozzle with a slitwidth of 0,5 mm without additional cost.

- for distributionsystem type DSAO, insatallationtype A, can also be supplied with baffle-distributor without additional cost.

Other Distributionsystem on request.